

US01 ORIGINAL NON-PROVISIONAL APPLICATION

Application Based on:

Docket No. 81392/LPK
Attorney: Lawrence P. Kessler
Inventors: Ralf Allner
Thomas Biber

**DEVICE FOR BALANCING OF A RADIAL THREADED
SPINDLE ECCENTRICITY OF A SPINDLE DRIVE**

Commissioner for Patents
ATTENTION: BOX PATENT APPLICATION
Washington, D.C. 20231

Express Mail Label No.: EL832732304US

Date: December 10, 2001

**Device for Balancing of a Radial Threaded Spindle Eccentricity
of a Spindle Drive**

Field of the Invention

5 The invention concerns a device for balancing a radial threaded spindle eccentricity of a spindle drive to avoid blocking of the spindle drive during the lifting movement of a platform, especially the lifting movement of the platform with objects in a machine.

Background of the Invention

10 Spindle drives are known in which the platform is mounted by several bearing devices arranged on it on several axiparallel spindles and can be moved together with the beating devices axially along the spindles and in which one of the spindles is a rotating threaded spindle on which a bearing device having a spindle nut is arranged and one of the bearing devices has radial play to balance the radial threaded spindle eccentricity.

15 EP-B1-0 024 944 discloses such a device for vertical lifting and lowering of a stack of flat objects (magnetic cards) in a card delivery machine, in which a platform or container carrying the stack can be moved by a spindle drive having a threaded spindle and a cylinder shaft in the vertical lifting direction and the platform during the
20 lifting movement is guided by the cylinder shaft arranged axiparallel to the threaded spindle and at a spacing from it and secured against horizontal pivoting. The platform is mounted on the threaded spindle by a spindle nut and on the cylinder shaft by a bearing bush.

25 In order to avoid jamming of the platform against the cylinder shaft caused by the threaded spindle eccentricity or blocking or stiff movement of the platform, the spindle nut is arranged freely moveable in the form of a rectangular block (spherical cap) in a pocket-like bearing cavity (in the region of a U-shaped recess) on one of the sides of the platform loosely, i.e., in a horizontal plane radially around the threaded spindle. The horizontal and radial movement freedom of the spindle nut relative to

the platform is slightly greater than the radial eccentricity of the threaded spindle.

A drawback of this disclosed variant is that because of the use of the single threaded spindle for the lifting movement of the platform carrying the stack, in heavy stacks tilting and therefore jamming or clamping of the platform against the cylinder shaft or the threaded spindle can occur. Moreover, high friction forces from surface friction between the spindle nut (spherical cap) and platform in the bearing cavity during horizontal radial movement of the spindle nut against the platform caused by the spindle eccentricity to occur because of the design of the bearing site in heavy stacks, which favor jamming of the platform against the cylinder shaft and causes high material abrasion at the bearing site.

Summary of the Invention

The underlying task of the invention is therefore to create a device that does not exhibit the mentioned drawbacks, but guarantees efficient lifting movement of a platform true to position and free of jamming even with heavy loads in an automatically operating machine and also has a simple low-wear design.

The task is solved according to the invention with a device wherein the spindle drive has at least three axiparallel, rotatable, threaded spindles with bearing devices with different or the same bearing clearance in a polygonal arrangement and low-friction bearing devices with radial bearing clearance are arranged to balance the radial eccentricity of the rotating threading spindles so that a relative radial movement of the rotating spindles relative to the platform is possible with limited friction force.

In a first bearing device, the platform is advantageously arranged essentially radially free of play on a first spindle, a second bearing device has radial bearing clearance on both sides of a second spindle, which is prescribed to run radially linear back-and-forth from the first spindle, and the third and additional bearing devices are arranged with radial bearing clearance effective all around the connected third and additional spindles; or in an alternative variant, all the bearing devices arranged on the threaded spindles of the platform have bearing clearance that is active radially all around.

The task is also solved with a device according to the invention wherein the bearing devices each have an annular ball bearing arranged concentrically around the spindle, by which the radial bearing clearance between the platform and the spindles to balance the threaded spindle eccentricity can be produced free of friction.

- 5 Advantageously the ball bearings each have a first plane bearing shell aligned perpendicular to the lifting movement and a second plane bearing shell aligned plane-parallel to the first, between which, held by an annular cage, the balls of the corresponding ball bearings are mounted to rotate freely, the first bearing shell of the ball bearing being rigidly connected to a spindle nut of the bearing device and the
- 10 second bearing shell being rigidly connected to the platform or in an alternative variant the bearing devices each have an annular bearing arranged concentrically around a threaded spindle, in which a first concave, ball-guiding bearing shell of the ball bearing is rigidly connected to the spindle nut and the second bearing shell is rigidly connected to the platform in a position plane-parallel to the first bearing shell
- 15 and has a plane contact side for the balls.

Additional features and advantages can be deduced from the description of the practical examples of the invention shown in the drawing and the additional subclaims.

Brief Description of the Drawings

- 20 In the detailed description of the preferred embodiment of the invention presented below, reference is made to the accompanying drawings, in which:

Figure 1 shows a spindle drive with the device according to the invention in a three-dimensional (schematic) view through an opening of a housing;

- 25 Figure 2 shows the device according to the invention according to Figure 1 in the view from the top and along a line A-A;

Figure 3 shows the device according to the invention according to Figure 2 in an enlarged partial view from the top and through an opening in the platform;

Figure 4a shows the device according to the invention according to Figures 2


and 3 in a partially opened side view from direction C1;


Figure 4b shows the device according to the invention according to Figures 2 and 3 in a side view from direction C2 along line B-B;


Figure 4c shows the device according to the invention according to Figure 4b
5 with an alternative variant of the bearing device with concave, ball-guiding bearing shell on the ball bearing; and

Figure 5 shows the device according to the invention according to Figure 2 in an alternative variant with limitation means to prevent horizontal movement of the platform.

Detailed Description of the Preferred Embodiments

 10
The following description according to Figures 1 to 5 refers to a preferred variant of the device according to the invention for balancing of a threaded spindle eccentricity in order to avoid blocking or jamming of a spindle drive I having several spindles, which is provided for lifting movement of a platform 2 carrying a sheet
15 stack S of a sheet feed magazine in an ordinary sheet processing machine (not shown), for example, a copier. Individual sheets can be automatically removed in succession from the sheet stack lying or positioned on the platform by an ordinary sheet removal/transport unit of the copier (not shown) and fed to one or more sheet processing stations of the copier.

 20
It is self-evident to one skilled in the art active in this field that the device according to the invention can also be used in other machines, for example, in delivery or feed devices for cards or other stackable objects, as well as in printers or sheet soiling machines.

 25
The device according to the invention having a spindle drive 1, depicted in Figure 1 in a three-dimensional schematic view through an opening of a machine housing 5, has an upper 51 and a lower 52 essentially rectangular bearing plate 2 within the machine housing 5 with four spindles mounted between them in axiparallel, vertical alignment V on four corner points of the bearing plates 51;52 in the form of threaded spindles G1; G2; G3; G4. The upper bearing plate 51 has a

recess for access to the top of sheet stack S by band and/or by sheet removal/transport unit, so that only an edge region of the bearing plate remains in the form of a U.

The platform 2 is mounted on corresponding threaded spindle G1; G2; G3; G4 by four bearing devices L1; L2; L3; L4 arranged on it, which according to Figure 2

5 have different radial bearing clearance F1; F2 in the horizontal direction X Y.

To hold and guide the sheet stack S, as shown in Figures 2 and 5, several adjustable side stops 23 and rear stops 24 are made on a bottom plate 20 arranged on platform 2, which extend in the lifting direction and act laterally on the sheet stack. These stops are omitted in Figure 1 for a clearer depiction of the invention.

10 Platform 2 can be lifted together with the bearing devices axially along the spindles vertically in direction Z, for which purpose all threaded spindles G1; G2; G3; G4 of the spindle drive 1 can be driven to rotate synchronously by a single microprocessor-control drive unit 6. The drive unit 6 is controllable by an ordinary control unit and sensor unit (not shown) of the copier in its rotational direction and

15 rotation time and has a drive motor 60 with a drive pinion, as well as a drive belt 61 in the form of a toothed belt that can be driven over the drive pinion. The toothed belt 61 then moves around all pulleys 62 which are arranged concentrically on the threaded spindles G1; G2; G3; G4 in the region of the lower bearing plate 52 and connected rigidly to them.

20 In the preferred variant of the invention according to Figures 1 and 2 a first bearing device L1 of the platform is arranged essentially radially and free of clearance on a first spindle G1, a second bearing device L2 according to Figures 1 to 4a has a radial bearing clearance F1 on both sides of the second spindle G2 in direction Y, which is prescribed to run radially linear back-and-forth from the first spindle G1 and the third and additional bearing devices L3, L4 according to Figures

25 1, 2, 4b and 4c are arranged with bearing clearance F2 effective all the way around (in direction X; Y) the corresponding third and additional spindles G3, G4. During the lifting movement of platform 2 during a spindle eccentricity of threaded spindles G1-G4, a horizontal movement of platform 2 is obtained in direction X or across the

transport direction T of sheet S (see Figure 2), which is determined by the spindle eccentricity of the threaded spindle G1 and G2 and a horizontal movement in direction Y or along the transport direction T, which is only determined by the spindle eccentricity from threaded spindle G1.

5 The bearing devices L1; L2; L3; L4 of platform 2 are arranged in the variant according to the invention as low-friction bearing devices with radial clearance F1; F2 to balance the radial eccentricity of the rotating threaded spindles G1; G2; G3; G4 so that a relative radial movement of the rotating spindle G1; G2; G3; G4 to platform 2 is possible with limited friction force and limited force expenditure. As shown in
10 Figures 3, 4a and 4c, the bearing devices L1; L2; L3; L4 then each have an annular ball bearing 3 arranged concentrically around spindles G1; G2; G3; G4, by which the radial bearing clearance F1 and F2 between platform 2 and the spindles can be produced to balance the threaded spindle eccentricity in low-fiction fashion.

As shown in Figures 3, 4a-4b, each ball bearing 3 has a first plane lower
15 annular bearing shell 31 aligned perpendicular to the lifting movement and a second plane upper annular bearing shell 32 aligned plane-parallel to the first; between which, the balls 34 of the ball bearings, held by an annular cage 33; 33.1; 33.2 are mounted to rotate freely, the first bearing shell 31 of ball bearing 3 being rigidly connected to a corresponding spindle nut M1; M2; M3; M4 of the bearing devices L1;
20 L2; L3; L4 and the second bearing shell 32 being rigidly connected to platform 2.

The bearing shells 31; 32 have a plane support width for ball 34 in the radial direction, which is larger than the maximum radial bearing clearance F1; F2 predetermined by the maximum spindle eccentricity and the ball cage 33 has an outer 33.1 and an inner 33.2 annular element around the balls 34 in a concentric
25 arrangement around spindle G1; G2; G3; G4 and around the spindle nuts M1; M2; M3; M4, the inner annular element 33.2 having an inside diameter that essentially corresponds to the outside diameter of spindle nut M1; M2; M3; M4.

In an alternative variant according to Figure 4c, the bearing devices L1; L2; L3; L4 each have an alternative annular ball bearing 4 arranged concentrically around

a threaded spindle G1; G2; G3; G4, which has a first lower, concave, ball-guiding bearing shell 41 of ball bearing 4, which is rigidly connected to a corresponding spindle nut M1; M2; M3; M4 of bearing device L1; L2; L3; L4, and whose second, upper bearing shell 42 is connected in a plane-parallel position relative to the first bearing shell 41 to platform 2 and has a plane support side for the freely rotating balls 44 of ball bearing 4.

The spindle nuts M1; M2; M3; M4 arranged on the threaded spindles G1; G2; G3; G4 and liftable by rotation of the spindle, as shown in Figures 4a and 4b, have a cylindrical shape or a cylindrical shaft extending axially to the axis of rotation of the spindle, a radially protruding cylindrical flange being applied concentrically on the lower end of each spindle nut. The lower/first annular bearing shell 31 is arranged lying on this flange of the spindle nut, centered by a concentric annular element of the flange having a smaller diameter and rigidly connected to the flange (for example, by press fitting from the inside periphery of bearing shell 31 to the outside periphery of the annular element).

Each upper/second annular bearing shell 32 of ball-bearing 33 is rigidly arranged on a bottom of platform 2 or its bearing sites L1; L2; L3; L4 in the region of a passage opening to the corresponding spindle G1; G2; G3; G4 in an annular recess, for example, by press fitting from the outside periphery of bearing shell 32 to the inside periphery of the recess of platform 2. The upper bearing shell 2 of ball bearing 3 and the spindle passage opening on platform 2 have an inside diameter of their passage opening whose radius is greater by the amount of required predetermined radial bearing clearance F1; F2 of the individual bearing sites of the bearing devices L1; L2; L3; L4 than a radius of the outside diameter of the upper cylinder shaft of spindle M1; M2; M3; M4 protruding upward through the passage openings. The outside diameter of the upper cylinder shaft of the spindle nut then also serves for centering and guiding of the inner annular element 33.2 of the annular ball cage 33.

A limitation of the radial bearing clearance F1; F2 between bearing devices L1; L2; L3; L4 of the bearing sites or platform 2 and the spindles G2; G3; G4 and the

spindle nuts M1; M2; M3; M4 can be produced by limiting devices 21; 22 of platform 2 arranged on platform 2 and engaging the spindle nuts radially outward, i.e., the inside edge of the spindle passage openings on the bearing sites L2; L3; L4 is a limiting device 21; 22 for the radial bearing clearance F1; F2.

5 In order to guarantee that the spindle nuts M1; M2; M3; M4 and thus the platform 2 can be moved upward and downward in one lifting movement, i.e., the spindle nuts are not corotated with the threaded spindles G1; G2; G3; G4, the spindle nuts are loosely coupled to the bearing sites L1; L2; L3; L4 or to platform 2 by holding devices, for example, in the form of mounting bolts 25 (see Figure 3). For
10 this purpose, the mounting bolt 25 is connected rigidly to the cylinder shaft of spindle nuts M2; M3; M4 and protrudes with its opposite end, freely mobile in the axial direction (according to the varying play F1) through a guide hole on a connector 26 of the platform or within the platform-bearing site L2; L3; L4. The guide hole is then
15 chosen in diameter large enough that the radial bearing clearance F2 is guaranteed through the circular horizontal movement of the mounting ball 25. An exception is the bearing site L1 with spindle nut M1, since this spindle nut can be rigidly and directly connected with its cylinder shaft to platform 2 because of the predetermined bearing site L1 free of clearance.

In another variant of the invention depicted in Figure 5, ball bearing devices
20 L1; L2; L3; L4 of platform 2 arranged on the threaded spindles G1; G2; G3; G4 and spindle nuts M1; M2; M3; M4 have identical or also nonidentical/different bearing clearance F2 that acts radially all the way around. For limitation of the radial bearing clearance F2 between the bearing devices 3; M1; M2; M3; M4 of the bearing sites L1; L2; L3; L4 and the spindles G1; G2; G3; G4 and to avoid horizontal radial
25 movement of platform 2 in the X/Y direction during its lifting movement, fixed limiting devices 50 on the apparatus side are arranged, which engage at right angles to the lifting movement on all four sides of the platform 2 or on the bottom plate 20 for the sheet stack stops 23; 24. The limitation devices 50 are, for example, ribs or connectors, as a component of the spindle drive housing 5 and extend over the entire

lifting height of platform 2 along the lifting movement.

- In another alternative variant of the invention (not shown), the spindles G1; G2; G3; G4 have a combination of threaded spindles and smooth cylinder shafts or cylinder columns, in which the cylinder shafts serve as a guide and as rotational
- 5 protection and tilting protection for platform 2. The spindle nuts are then replaced by guide sleeves on the cylinder shafts. In addition, only three instead of four spindles are provided in a polygonal or triangular arrangement.

5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000

Parts list

	F1	Radial bearing play having two degrees of freedom on second bearing device
	F2	Radial all-round bearing clearance on third and fourth bearing device
	G1	First threaded spindle of spindle drive
5	G2	Second threaded spindle of spindle drive
	G3	Third threaded spindle of spindle drive
	G4	Fourth threaded spindle of spindle drive
	L1	First bearing device (bearing site) of the platform
	L2	Second bearing device (bearing site) of the platform
10	L3	Third bearing device (bearing site) of the platform
	L4	Fourth bearing device (bearing site) of the platform
	M1	First spindle nut on first threaded spindle/on first bearing device
	M2	Second spindle nut on second threaded spindle/on second bearing device
	M3	Third spindle nut on third threaded spindle/on third bearing device
15	M4	Fourth spindle nut on fourth threaded spindle/on fourth bearing device
	S	Sheet-like, plate-like objects/object (stacked)
	T	Horizontal transport direction of the objects/sheets from the stack
	X	First horizontal movement direction of the platform
	Y	Second horizontal movement direction of the platform
20	Z	Vertical lifting direction of the platform/spindle drive
	1	Spindle drive with platform
	2	Platform to accept/release objects (sheet/plate stack)
	3	Annular ball bearing with ball cage and plane bearing shell (bearing devices)
	4	Alternative/annular ball bearing with concave/ball-guiding bearing shell
25	5	Housing of the spindle drive
	6	Drive unit for threaded spindle for the spindle drive
20		Bottom plate of the platform for side/rear stops (sheet/plate stack)
21		First limitation means for radial bearing plate F1/platform movement (component of the platform)

- 22 Second limitation means for radial bearing plate F2/platform movement
(component of the platform)
- 23 Side stop/stops on bottom plate for object/sheets
- 24 Rear stop/stops on bottom plate for object/sheet
- 5 25 Mounting bolt for spindle nut mount and guide on platform
- 26 Connector/rib on platform for mounting bolt-guide
- 30
- 31 First/lower plane bearing shell of the ball bearing
- 32 Second/upper plane bearing shell of the ball bearing
- 10 33 Annular cage for the balls
- 33.1 Outer annular element of the cage
- 33.1 [sic] Inner annular element of the cage
- 34 Balls of the ball bearing
- 40
- 15 41 First/lower concave, ball-guiding bearing shell (alternative ball bearing)
- 42 Second/upper plane bearing shell of the alternative ball bearing
- 43
- 44 Balls of the alternative ball bearing
- 50 Alternative limitation means for platform (component of the spindle drive
housing)
- 20 51 Upper bearing plate for the threaded spindle
- 52 Lower bearing plate for the threaded spindle
- 60 Drive motor of the threaded spindle drive unit
- 61 Drivebelts
- 25 62 Pulley on threaded spindle